



## APPLICATIONS

**Eni Geum NG 40** is a lubricant for modern stationary engines, spark-ignition type, burning natural gas, methane or biogas where a low ash oil is required.

**Eni Geum NG 40** is formulated with high Viscosity Index basestocks and selected additives that deliver detergent-dispersant, antiwear and antifoam properties. The product retains a particularly high resistance to oxidation processes.

## CUSTOMER ADVANTAGES

- Prevention of deposits and laques formation on pistons and valves for an outstanding engine cleanliness
- Protection of lubricated components from mechanical wear
- Particularly extended oil drain intervals

## SPECIFICATIONS - APPROVALS

- MWM
- GE Jenbacher engines type 2/3/4/6 on gas class A and B
- Wartsila





## CHARACTERISTICS

Properties	Method	Unit	Typical
Appearance	APM 27	-	clear
Density at 15°C	ASTM D 4052	kg/m <sup>3</sup>	874
Viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	13.6
Viscosity Index	ASTM D 2270	-	111
Pour point	ASTM D 97	°C	-30
B. N.	ASTM D 2896	mgKOH/g	5.4
Sulphated ash	ASTM D 874	% (m/m)	0.50



eni