



**Product Data**

## **Alpha LCG 150 BX**

Industrial EP Gear Oils

### **Description**

Alpha LCG 150 BX is a zinc and chlorine free ashless extreme pressure oil formulated for industrial gear lubrication where enhanced yellow metal corrosion inhibition is a prime requirement.

### **Application**

It is designed specifically for use in metal can body making machines where cross contamination with water miscible forming fluids can arise.

### **Advantages**

- Advanced sulphur/phosphorus technology
- High level of anti-wear and extreme pressure protection
- Improved thermal stability
- Excellent rust protection
- Higher oxidation resistance
- Inhibited against phosphor/bronze corrosion
- Improved component life protection

Typical Characteristics

| Name                                     | Method                 | Units                                   | Alpha LCG 150 BX |
|------------------------------------------|------------------------|-----------------------------------------|------------------|
| ISO viscosity grade                      | -                      | -                                       | 150              |
| Density @ 20°C / 68°F                    | ISO 12185 / ASTM D4052 | kg/m³                                   | 890              |
| Kinematic Viscosity @ 40°C / 104°F       | ISO 3104 / ASTM D445   | mm²/s                                   | 150              |
| Kinematic Viscosity @ 100°C / 212°F      | ISO 3104 / ASTM D445   | mm²/s                                   | 14.5             |
| Viscosity Index                          | ISO 2909 / ASTM D2270  | -                                       | 95               |
| Flash Point - closed cup method          | ISO 2719 / ASTM D93    | °C/°F                                   | 190/374          |
| Pour Point                               | ISO 3016 / ASTM D97    | °C/°F                                   | -18/0            |
| Foam Sequence I - tendency / stability   | ISO 6247 / ASTM D892   | ml/ml                                   | 20/0             |
| Rust test - synthetic seaw ater (24 hrs) | ISO 7120 / ASTM D665B  | Rating                                  | Pass             |
| Copper corrosion (3 hrs@100°C/212°F)     | ISO 2160 / ASTM D130   | Rating                                  | 1                |
| Elastomer Compatibility - w ith SRE-NBR1 | ISO 6072 / ASTM D3604  | % volume change / shore hardness rating | 0.5 / -2         |
| FZG Gear Scuffing test - A/8.3/90        | ISO 14635-1            | Failure Load Stage                      | >12              |

Subject to usual manufacturing tolerances.

Alpha LCG 150 BX  
16 Dec 2022  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

http://msdspds.castrol.com