

**Product Data****Duratec L**

Gas Engine Lubricant

Description

Duratec L is a mineral based SAE 40 low ash gas engine lubricant.

Application

Duratec L is formulated primarily for spark ignition natural gas engines where a low ash formulation is specified and where the gas is largely free from aggressive components i.e. halogens and hydrogen sulphide.

The detergent/dispersant additive system has been designed to control deposit formation and improve oxidation characteristics whilst protecting the engine against corrosion and offering good TBN retention.

Duratec L is approved or meets requirements with the following OEMs. All are for natural gas types unless specified.

- Deutz - all engines
- Himsen - all engines
- INNIO Jenbacher - type 2 and 3 (gas types A, B and CAT), type 4A (gas types A, B and CAT), type 4B and 4D (gas types A, B, C and CAT), type 6C and 6E (gas types A, B, C and CAT) engines *
- INNIO Waukesha - 12V220GL and 18V220GL engines **
- MTU - series 4000 - L32, L33, L61, L62 and L63 engines
- MWM - TCG 2016, 2020 and 2032 engines
- Caterpillar - CG132, 170 and 260 engines
- Wärtsilä 175SG, 220SG, 25SG, 28SG, 34SG and 50SG
- Wärtsilä 32DF and 50DF dual fuel engines (running predominantly on natural gas)
- Perkins
- Rushton

* Gas type A (Natural Gas), gas type B (biogas/ sewage gas), gas type C (landfill gas), CAT: if an oxidation catalytic converter is included in the scope of supply

** Pipeline quality Natural Gas

Advantages

- Reduces deposits & maintains engine cleanliness shown by multiple OEM engine trials and extensive field experience
- Possesses good thermal and oxidative stability ¹
- Provides good resistance to acid corrosion¹
- Excellent antiwear characteristics ¹

¹ as demonstrated during multiple OEM approval trials and field installations

Typical Characteristics

Name	Method	Units	Duratec L
Appearance	Visual	-	Clear and Bright
Density @ 15°C	ISO 12185 / ASTM D4052	kg/m3	890
Kinematic Viscosity, 100°C	ISO 3104 / ASTM D445	mm²/s	13.0
Kinematic Viscosity, 40°C	ISO 3104 / ASTM D445	mm²/s	125
Viscosity Index	ISO 2909 / ASTM D2270	None	97
Base Number	ISO 3771 / ASTM D2896	mg KOH/g	4.5
Flash Point, closed cup method	ISO 2719 / ASTM D93	°C	225
Pour Point	ISO 3016 / ASTM D5985	°C	-18
Sulphated Ash content	ISO 3987 / ASTM D874	% w t	0.45

Subject to usual manufacturing tolerances

Duratec L
16 Jan 2025
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

<http://msdspds.castrol.com>